

Sony SNC-DH210 POE Colour 3MP Vari-Focal IP Day/Night Dome Camera

- ✓ 1080P Dual-Stream
- ✓ Exmor CMOS Sensor
- ✓ H.264, MPEG4, Jpeg
- ✓ 0.4Lux Colour, 0.25Lux B/W with
3.1-8.9mm AI Vari-Focal Lens
- ✓ AGC
- ✓ ATW-Pro
- ✓ DNR
- ✓ EV Compensation
- ✓ PoE Only



The SNC-DH210 is an indoor high definition (1080p, supporting H.264 at 15fps) 3 Megapixel (2048 xx 1536 maximum resolution) compact mini-dome camera with Electrical Day/Night function, DEPA and ONVIF compliance. It supports dual streaming and triple codec encoding.

Sony's Exmor CMOS sensor provides excellent pictures and event detection for effective evidence gathering.

Sony's X-Series cameras have outstanding picture quality and a compact, affordable, stylish design.

Compact and Stylish design

A compact, stylish and discreet design that compliments any surveillance environment.

DEPA

The SNC-DH210 offers intelligent video analytics, based on the Sony DEPA platform. DEPA is a combined function of the intelligence built in to the camera and rules/filters that determine which images should be recorded or when an alarm should be triggered.

EXMOR and CMOS Sensor

High resolution CMOS sensor with low noise characteristics for improved image acquisition. Derived from Sony's broadcast product range, EXMOR is one of the highest quality image sensors available.

Power over Ethernet (PoE) capability

Supporting Power over Ethernet (PoE), the camera can be powered using the same Ethernet cable it uses for data transfer. This feature greatly reduces the physical infrastructure costs and speed of deployment.

ONVIF (Open Network Video Interface Forum) compliance

The ONVIF (Open Network Video Interface Forum) defines a common protocol for the exchange of information between network video devices including automatic device discovery and video streaming. Allows interoperability between network video devices.

Full HD (1920x1080p) resolution

Detailed Full HD progressive images. Progressive acquisition (as opposed to interlace) means that images are more stable to view, contain more information and compress more efficiently - without "interlace artifacts".

Supports multiple industry standard codecs: H264, MPEG-4 and JPEG with dual streaming capability

This multi-codec camera supports three compression formats: JPEG, the best choice of high-quality still images; MPEG-4, the format that provides clear moving images efficiently over limited-bandwidth networks; and H.264, the alternative for severely limited-bandwidth networks, providing twice the efficiency of MPEG-4. The camera can generate multiple streams simultaneously.

Stream Squared Function

An incredibly useful function that allows simultaneous streaming of two 4:3 aspect ratio videos in user-selectable SD resolutions. You can select the entire image or a portion of the image from the original view and resize to SD resolution. With this feature the SNC-DH220 can replace two SD cameras installed in the same line of view.

Electrical Day/Night

Ensures that the camera is operating with the optimum sensitivity for both day and night conditions.

Analogue Monitor Output

This allows an analogue video monitor to be connected directly to the camera.